

Hydrogen peroxide probe

HC2A-S(M)-HH




- Advantages
- Measures relative humidity, temperature and dew-point
  - With HYGROMER HH1-SK sensor for hydrogen peroxide
  - Advanced probe housing and construction
  - Hot-swappable: fast exchange without adjustment

- Decontamination & sterilization processes of biohazardous material
- Sterelization of medical equipment, incubators and clean rooms
  - Pharmaceutical industry



Hydrogen Peroxide Probe HC2A-S-HH

- Application Range: 0...100 %rh, 0...60 °C
- Accuracy: ±1.0 %rh, ±0.1 K @ 10...30 °C
- Materials: PPS




Order code	Probe diameter	Probe length	Probe length with filter carrier	Sensor element
HC2A-S-HH	Ø 15 mm	65 mm	108 mm	HYGROMER HH1-SK

 Delivery package: With filter carrier (SPA-PCB), without filter. Filters must be purchased additionally.

Hydrogen Peroxide Probe HC2A-SM-HH

- Application Range: 0...100 %rh, 0...60 °C
- Accuracy: ±1.0 %rh, ±0.1 K @ 10...30 °C
- Materials: stainless steel 1.4301



Order code	Probe diameter	Probe length	Probe length with filter carrier	Sensor element
HC2A-SM-HH	Ø 15 mm	65 mm	108 mm	HYGROMER HH1-SK

 Delivery package: With filter carrier (SPA-SS), without filter. Filters must be purchased additionally.

Computer Connection

- The cable AC3001 allows direct connection to a computer via USB and, with use of the HygroSoft software to adjust the HC2A-S(M)-HH probe's parameters such as
- Scale of analog outputs
  - Calculated parameter on analog outputs

ProcessSensing.com

rotronic


MEASUREMENT SOLUTIONS

A PST BRAND

Technical Information

Order code	HC2A-S-HH / HC2A-SM-HH
Type	Humidity-Temperature-Probe for HH
Humidity Sensor	HYGROMER HH1-SK
Temperature Sensor	PT100 1/3 class B
PeakLoad H <sub>2</sub> O <sub>2</sub>	880 ppm / 1200 mg/m <sup>3</sup>
Operating humidity	0...100 %rh
Operating temperature	0...60 °C
Accuracy @10...30°C before and after diffusion phase	±1.0 %rh, ±0.1 K
Analogue output	2 x 0...1 VDC
Analogue output parameter	<ul style="list-style-type: none"><li>Humidity (default)</li><li>Temperature (default)</li><li>Dew-point (setting with HygroSoft)</li><li>Frost-point (setting with HygroSoft)</li></ul>
Analog output scaling	<ul style="list-style-type: none"><li>Humidity (0...100 %rh = 0...1 V)</li><li>Temperature (-40...60 °C = 0...1 V)</li><li>Freely settable with HygroSoft</li></ul>
Timing	Measurement interval of 1 s
Air Chip 3000	Saves adjustment data so that probes can be interchanged without re-adjusting
Housing material	Polycarbonat / Stainless steel 1.4301
Filter	No Filter
Audit Trail	FDA CFR21 Part 11 /GAMP comatible


Connector pin-out




Possible Extension Cables

It is possible to extend the distance between the probe and its reading device with extension cable.

- Passive connections are possible up to 5 m (see table below for possible options).
- An amplifier cable (AC3003) allows connections up to 50 m.



Order Code	Cable Length	Color
E2-01A	1 m (0.95 - 1.05 m)	Black
E2-02A	2 m ( 1.92 - 2.08 m)	
E2-05A	5 m ( 4.85 - 5.15 m)	
E3-01A	1 m (0.95 - 1.05 m)	White
E3-05A	5 m ( 4.85 - 5.15 m)	



Order Code	Description	Cable Length
AC3003	Signal amplifier, probe and instrument side with luster terminal	Self assembly
AC3003/10	AC3003 with luster terminal and Cat. 5 cable	10 m (9.8 - 10.2 m)
AC30003/50		50 m

Subject to technical change without notice. Printing and other errors reserved.