

E+E

—
your partner
in sensor
technology.

+ Datasheet EE210

**Humidity and Temperature Sensor
for Demanding Climate Control**



www.epluse.com

GET UP TO 30% DISCOUNT + AN EXTRA 10% CASH VOUCHER

QUOTATION

SALES@MIIGO.ONLINE

II

+91-9398693085

EE210

Humidity and Temperature Sensor for Demanding Climate Control

The EE210 humidity (RH) and temperature (T) sensor is designed to meet the highest requirements in demanding climate control applications. Besides the accurate measurement of RH and T EE210 calculates various RH related parameters such as dew point temperature, absolute humidity and mixing ratio.

Outstanding Measurement Performance

Excellent performance of EE210 in polluted or aggressive environment is ensured by the encapsulated measurement electronics inside the sensing probe and the long-term stable E+E sensing element with proprietary coating.

Analogue, Digital Outputs and Display

All measured and calculated values are available on the RS485 interface with Modbus RTU protocol, two of them on the analogue voltage or current outputs, while up to three values can be shown simultaneously on the optional display.

Versatility

EE210 is available for wall or duct mount, with remote probe, as well as an outdoor version. The IP65/NEMA 4X enclosure minimizes installation costs and provides outstanding protection against contamination and condensation.

Easy Configuration and Adjustment

With an optional USB-C configuration stick, the user can set the RS485 interface parameters and output scaling, perform an offset or two point adjustment for RH and T and change display layout.



EE210 wall mount (type T1)



EE210 duct mount (type T2)




EE210 with remote probe (type T3)



EE210 outdoor with radiation shield (type T13)

Features



Inspection certificate
according DIN EN 10204-3.1

www.epluse.com

v2.15 / All rights reserved | 3


GET UP TO 30% DISCOUNT + AN EXTRA 10% CASH VOUCHER

QUOTATION SALES@MIIGO.ONLINE || +91-9398693085

Features

Protective Sensor Coating


The E+E proprietary sensor coating is a protective layer applied to the active surface of the sensing element. The coating substantially extends sensor lifetime and ensures optimal measurement performance in corrosive environment (salts, off-shore applications). Additionally, it improves the sensors' long term stability in dusty, dirty or oily applications by preventing stray impedance caused by deposits on the active sensor surface.




Dimensions

Values in mm (inch)

Type T1 (wall mount)



Type T2 (duct mount)






L = filter cap length	mm (inch)
Membrane	34 (1.4)
Stainless steel	33 (1.3)
Metal grid	33 (1.3)

Technical Data

Measurands

Relative humidity (RH)	
Measuring range	0...100 % RH
Accuracy ¹⁾ incl. hysteresis, non-linearity and repeatability	
Type T1, T2 -15...+40 °C (+5...+104 °F), ≤90 %RH	±(1.3 + 0.003*measured value) %RH
-15...+40 °C (+5...+104 °F), >90 %RH	±2.3 %RH
-40...+60 °C (-40...+140 °F)	±(1.5 + 0.015*measured value) %RH
Type T3 @ 20 °C (68 °F)	±2.5 %RH
Type T13 -15...+40 °C (+5...+104 °F), ≤90 %RH	±(1.6 + 0.005*measured value) %RH
-15...+40 °C (+5...+104 °F), ≥90 %RH	±3 %RH
-40...+60 °C (-40...+140 °F)	±(2.3 + 0.008*measured value) %RH

1) Traceable to international standards, administrated by NIST, PTB, BEV,...
The accuracy statement includes the uncertainty of the factory calibration with an enhancement factor k=2 (2-times standard deviation).
The accuracy was calculated in accordance with EA-4/02 and with regard to GUM (Guide to the Expression of Uncertainty in Measurement).
For Type T13: @ 24 V DC and RL=250 Ω for A6 Versions.

Temperature (T)	
Measuring range	
Type T1, T2, T13 Type T3 (probe) Type T3 (enclosure)	-40...+60 °C (-40...+140 °F) -40...+80 °C (-40...+176 °F) -40...+60 °C (-40...+140 °F)
Accuracy	
Type T1,T2	
Type T3	
Type T13	

Technical Data

Measurands

Calculated measurands		from		up to		unit	
Dew point temperature	Td ¹⁾	-40	(-40)	60	(140)	°C	(°F)
Frost point temperature	Tf ²⁾	-40	(-40)	0	(32)	°C	(°F)
Wet bulb temperature	Tw	0	(32)	60	(140)	°C	(°F)
Water vapour partial pressure	e	0	(0)	200	(3)	mbar	(psi)
Mixing ratio	r	0	(0)	160	(1200)	g/kg	(gr/lb)
Absolute humidity	dv	0	(0)	150	(60)	g/m ³	(gr/ft ³)
Specific enthalpy	h	-40	(-10)	500	(200)	kJ/kg	(BTU/lb)

1) Td accuracy according to RH and T uncertainties, please use the [E+E Humidity Calculator](#) for details.
2) Equals Td above 0 °C (32 °F).

Outputs

Analogue			
Two freely selectable and scalable outputs	0 - 5 V / 0 - 10 V	-1 mA < I _L < 1 mA	I _L = load current
	4 - 20 mA (2-wire)	R _L ≤ 500 Ω	R _L = load resistance
	0 - 20 mA (3-wire)	250 ≤ R _L ≤ 500 Ω recommended for type T13	
Digital			
Digital interface	RS485 (EE210 = 1 unit load)		
Protocol	Modbus RTU		
Factory settings	Baud rate according to ordering guide, parity even, 1 stop bit, Modbus address 242		
Supported Baud rates	9 600, 19 200 and 38 400		
Data types for measured values	FLOAT32 and INT16		

Technical Data

General


Power supply class III  USA & Canada: Class 2 supply necessary, max. voltage 30 V DC	4 - 20 mA (2-wire)		(10 V + R _L * 20 mA) < V+ < 30 V DC for type T13: 24 V DC ±10 % recommended
	0 - 5 V / 0 - 10 V 0 - 20 mA (3-wire) RS485		15 - 35 V DC or 24 V AC ±20%
Current consumption at 24 V	Voltage output	DC supply max. 12 mA AC supply max. 34 mA _{rms}	with display max. 23 mA with display max. 49 mA _{rms}
	Current output 2-wire	DC supply max. 40 mA	with display max. 40 mA
	Current output 3-wire	DC supply typ. 33 mA AC supply typ. 65 mA _{rms}	with display max. 44 mA with display max. 84 mA _{rms}
	Digital interface	DC supply typ. 5 mA AC supply typ. 15 mA _{rms}	with display max. 20 mA with display max. 35 mA _{rms}
Electrical connection		Screw terminals, max. 1.5 mm ²	
Cable gland		M16x1.5	
Display¹⁾		Available for type T1 / T2 / T3 1, 2 or 3 lines, user configurable Optional with backlight	
Temperature ranges			Without display
	Operation	-40...+60 °C (-40...+140 °F)	-20...+50 °C (-4...+122 °F)
		-40...+80 °C (-40...+176 °F) for probe PE210	-40...+80 °C (-40...+176 °F) for probe PE210
	Storage	-40...+60 °C (-40...+140 °F)	-20...+60 °C (-4...+140 °F)
Enclosure	Material Protection rating	PC (Polycarbonate), UL94 V-0 (with display UL94 HB) approved IP65 / NEMA 4X	
Electromagnetic compatibility		EN 61326-1 FCC Part15 Class A	EN 61326-2-3 ICES-003 Class A Industrial environment
Conformity		 	

1) For display operation with EE210-M1xA6 (4 - 20 mA, 2-wire) both outputs must be connected.


Dimensions

Values in mm (inch)


Type T3 (remote probe)




PE210




Type T13 (outdoor)



Mounting flange
in the scope of supply for type T2 and T3



Radiation shield HA010501 for type T13 (outdoor)
needs to be ordered separately



Ordering Guide

Feature	Description	Code			
Hardware Configuration		EE210-			
	Model	RH + T			
	Type	Wall mount	T1		
		Duct mount		T2	
		Remote probe ¹⁾			T3
		Outdoor			T13
	Probe length	50 mm (1.97")		L50	
		200 mm (7.84")		L200	
	Output	0 - 5 V	A2		
		0- 10 V	A3		A3
		0 - 20 mA (3-wire)	A5		
		4 - 20 mA (2-wire)	A6		A6
		RS485	J3		
	Filter	Membrane	F2		
		Metal grid	F3		F3
		Stainless steel sintered	F4		
	Display ²⁾	Without display	No code		
		Without backlight ³⁾	D1		
		With backlight ⁴⁾	D2		
Setup Analogue Outputs	Output 1 measurand	Relative humidity RH [%]	No code		
		Temperature T [°C]	MA1		
		Temperature T [°F]	MA2		
		Other measurands (xx see measurand code)	MAxx		
	Output 1 scaling low	0	No code		
		Value	SALValue		
	Output 1 scaling high	100	No code		
		Value	SAHValue		
	Output 2 measurand	Temperature T [°C]	No code		
		Temperature T [°F]	MB2		
		Other measurands (xx see measurand code)	MBxx		
	Output 2 scaling low	Value	SBLValue		
	Output 2 scaling high	Value	SBHValue		
Setup RS485	Protocol	Modbus RTU ⁵⁾	P1		
	Baud rate	9600	BD5		
		19200	BD6		
		38400	BD7		
	Units	Metric (SI)	No code		
		Non metric (US/GB)	U2		

1) The PE210 probe has to be ordered as separate position.
2) Factory setup: For analogue output versions the display shows the measurands selected for output 1 and output 2.
For digital output versions the display shows RH and T.
3) Not with output A5.
4) Not with output A6.
5) Modbus Map and setup instructions: See User Guide and Modbus Application Note at www.epluse.com/ee210.

Ordering Guide PE210

Feature	Description	Code
HW Configuration		PE210-
	Model	M1
	Filter	F2
		F3
		F4
	Connection cable length	KL150
		KL300

Measurand Code

For Output 1 and 2 in the Ordering Guide

Measurand	Unit	Code
		MAxx / MBxx
Relative humidity	%	10
Temperature	°C °F	1 2
Dew point	Td °C °F	52 53
Frost point	Tf °C °F	65 66
Mixing ratio	r g/kg gr/lb	60 61
Absolute humidity	dv g/m³ gr/ft³	56 57
Wet bulb temperature	Tw °C °F	54 55
Water vapour partial pressure	e mbar psi	50 51
Specific enthalpy	h kJ/kg BTU/lb	62 64

 PLEASE NOTE

No mix of SI/US units allowed.

Order Examples

Type T1 and T2

EE210-M1T1A3F2D2SBL-40SBH60

Feature	Code	Description
Model	M1	RH + T
Type	T1	Wall mount
Output	A3	0 - 10 V
Filter	F2	Membrane
Display	D2	With backlight
Output 1 measurand	No code	Relative humidity RH [%]
Output 1 scaling low	No code	0 %RH
Output 1 scaling high	No code	100 %RH
Output 2 measurand	No code	Temperature T [°C]
Output 2 scaling low	SBL-40	-40 °C
Output 2 scaling high	SBH60	60 °C

Order Examples

Type T3 Position 1: Basic Device

EE210-M1T3A6MB52SBL-10SBH50

Feature	Code	Description
Model	M1	RH + T
Type	T3	Remote probe
Output	A6	4 - 20 mA (2-wire)
Display	No code	Without display
Output 1 measurand	No code	Relative humidity RH [%]
Output 1 scaling low	No code	0 %RH
Output 1 scaling high	No code	100 %RH
Output 2 measurand	MB52	Dew Point Temperature Td [°C]
Output 2 scaling low	SBL-10	-10 °C
Output 2 scaling high	SBH50	50 °C

Position 2: Remote Probe

PE210-M1F3KL150

Feature	Code	Description
Model	M1	RH + T
Filter	F3	Metal grid
Connection cable length	KL150	1,5 m (4.9 ft)

Type T13 Position 1:

EE210-M1T13A6F3SBL-40SBH60

Feature	Code	Description
Model	M1	RH + T
Type	T13	Outdoor
Output	A6	4 - 20 mA (2-wire)
Filter	F3	Metal grid
Display	No code	Without display
Output 1 measurand	No code	Relative humidity RH [%]
Output 1 scaling low	No code	0 %RH
Output 1 scaling high	No code	100 %RH
Output 2 measurand	No code	Temperature T [°C]
Output 2 scaling low	SBL-40	-40 °C
Output 2 scaling high	SBH60	60 °C

Position 2:

HA010501

Radiation shield for EE210 Outdoor.

Accessories

For further information refer to [“Accessories”](#) the datasheet.

Accessories	Code
USB-C configuration stick	HA011070
Product Configuration Software (Free download: www.epluse.com/pcs10)	PCS10
Radiation shield for EE210 Outdoor (Type T13)	HA010501
Power supply adapter	V03
Protection cap for Ø12 mm probe	HA010783

Company Headquarters &
Production Site

E+E Elektronik Ges.m.b.H.
Langwiesen 7
4209 Engerwitzdorf | Austria
T +43 7235 605-0
F +43 7235 605-8
info@epluse.com
www.epluse.com

Subsidiaries

E+E Sensor Technology (Shanghai) Co., Ltd.
T +86 21 6117 6129
info@epluse.cn

E+E Elektronik France SARL
T +33 4 74 72 35 82
info.fr@epluse.com

E+E Elektronik Deutschland GmbH
T +49 6171 69411-0
info.de@epluse.com

E+E Elektronik India Private Limited
T +91 990 440 5400
info.in@epluse.com

E+E Elektronik Italia S.r.l.
T +39 02 2707 86 36
info.it@epluse.com

E+E Elektronik Korea Ltd.
T +82 31 732 6050
info.kr@epluse.com

E+E Elektronik Corporation
T +1 847 490 0520
info.us@epluse.com



—
your partner
in sensor
technology.

datasheet_EE210 | Version v2.15 | 11-2024
© Copyright E+E Elektronik Ges.m.b.H. | All rights reserved.

www.epluse.com

GET UP TO 30% DISCOUNT + AN EXTRA 10% CASH VOUCHER

QUOTATION SALES@MIIGO.ONLINE || +91-9398693085